

AM2

Photocatalyst composite for purificn. and sterilisation applications -
comprising substrate with photocatalyst particles adhered to its surface
using degradation resistant adhesive

Patent Assignee: FUJISHIMA A (FUJI-I); HASHIMOTO K (HASH-I); ISHIHARA
SANGYO KAISHA LTD (ISHH)

Inventor: FUJISHIMA A; FUKUI Y; HASHIMOTO K; MURAKAMI H; MURASAWA S;
WATANABE M

Number of Countries: 023 Number of Patents: 008

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Main IPC	Week
EP 633064	A1	19950111	EP 94109759	A	19940623	B01J-035/00	199506 B
AU 9464810	A	19950105	AU 9464810	A	19940617	C09J-011/04	199508
CA 2126418	A	19941229	CA 2126418	A	19940621	B01J-035/02	199513
JP 7171408	A	19950711	JP 94165836	A	19940627	B01J-035/02	199536
US 5547823	A	19960820	US 94266464	A	19940627	G03C-001/725	199639
			US 95555548	A	19951109		
TW 279175	A	19960621	TW 94105729	A	19940623	C09J-201/00	199640
AU 676299	B	19970306	AU 9464810	A	19940617	C09J-011/04	199718
CN 1101591	A	19950419	CN 94109013	A	19940627	B01J-035/02	199724

Priority Applications (No Type Date): JP 93291212 A 19931026; JP 93181834 A
19930628

Cited Patents: 03Jnl.Ref; JP 3008448; JP 5146671; JP 5253544; US 4544470

Patent Details:

Patent Kind Lan Pg Filing Notes Application Patent

EP 633064 A1 E 15

Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC
NL PT SE

JP 7171408 A 10

US 5547823 A 9 Cont of US 94266464

AU 676299 B Previous Publ. AU 9464810

Abstract (Basic): EP 633064 A

A photocatalyst composite comprises a substrate with photocatalyst particles adhered to it via a less degradative adhesive. Also claimed are (1) a process for producing a photocatalyst composite comprising disposing photocatalyst particles and a degradation-resistant adhesive on the substrate then fixing the adhesive to adhere the particles to the substrate; (2) a process for producing a photocatalyst composite comprising coating the substrate with a first layer of adhesive that is free of photocatalyst particles and fixing the adhesive, then applying a second layer of adhesive contg. photocatalyst particles and fixing the second layer adhesive; (3) a coating compsn. comprising a dispersion of the above particles and adhesive in a solvent; and (4) compsn. (3) further contg. a coupling agent.

PREFERRED COMPOSITE - The substrate may also have an absorbent adhered to its surface by the adhesive. The substrate may have a first layer of adhesive, pref. as above and optionally contg. inorganic particles, and a second layer comprising adhesive as above and photocatalyst particles. The photocatalyst particles comprise 5-98

vol.% of the vol. of adhesive and photocatalyst particles. **PREFERRED ADHESIVE** - A fluorinated polymer, pref. a copolymer of a vinyl ether and/or a vinyl ester and a fluoroolefin, a silicone-based polymer or an inorganic adhesive, pref. cement, is used. **PREFERRED CATALYST** - The photocatalyst particles are of TiO_2 , pref. contg. V, Fe, Co, Ni, Cu, Zn, Ru, Rh, Pd, Ag, Pt or Au or their cpds. or a mixt. as a second component inside the photocatalyst particles and/or on their surface.

USE - The composite is used in the decompns. and purificn. of harmful, malodorous or oily materials, and in purificn. and sterilisation of waste prods. They can be used for air and water purificn.

ADVANTAGE - The use of an adhesive that is not degraded by the catalyst allows the catalyst to be fixed to a substrate for long periods of time without affecting its activity. The catalyst can be adhered to substrates that are not suitable for prior art, high-temp. processes because are not heat-resistant, e.g. plastics or office walls, or they are difficult to heat.

Dwg.0/1

Abstract (Equivalent): US 5547823 A

A photocatalyst composite comprising a substrate having photocatalyst particles of titanium oxide adhered on it via an adhesive of fluorinated polymers, the photocatalyst particles containing a second component of at least one selected from the group consisting of metals and metal compounds of V, Fe, Co, Ni, Cu, Zn, Ru, Rh, Pd, Ag, Pt and Au, inside and/or on the surfaces of it, and the content of the photocatalyst particles being in the range of 50-98% by volume based on the total amount of the photocatalyst particles and the fluorinated polymers.

Dwg.0/1

Derwent Class: A14; A26; A81; G03; J04; P34; P83

International Patent Class (Main): B01J-035/00; B01J-035/02; C09J-011/04; C09J-201/00; G03C-001/725

International Patent Class (Additional): A61L-002/10; A61L-002/16; A61L-009/20; B01D-053/86; B01J-021/06; B01J-023/02; B01J-031/06; B01J-037/02; C08K-003/10; C09J-001/00; C09J-127/00; C09J-127/12